

Technical Data Sheet

ADDAPTOL™ DB Coalescing Agent

Article number: AT86948
Verification date: 18/02/2025
Version: 3.1

Typical chemical and physical properties

Non-VOC oxygenated solvent for use as a coalescing agent in waterborne systems and tail solvent in solvent borne systems.

Proprietary mixture of branched esters of dibasic acids.

Appearance Liquid
Active content ~100%

Water content <0,10 vol%

Acid value <0,30 mg KOH/g

 Density at 25°C
 1,02 - 1,06
 g/ml

 Viscosity at 25°C
 75 - 150
 mPa⋅s

 Colour
 <25</td>
 APHA

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and

treat level Markets Coating industry

Cleaning industry Ink industry

Applications Waterborne coatings

Solvent borne coatings Printing ink solvent Cleaner solvent

Recommended dosage/usage Depends on MFFT of binder.

Key benefits

- Readily biodegradable -- VOC free -

High thermal, hydrolytic and pH stability.

Generally, less ADDAPTOL™ DB is needed compared to conventional coalescing agents.

Compared to 2,2,4-trimethylpentanediol mono-isobutyrate, ADDAPTOL™ DB shows the following improved characteristics in waterborne coatings:

- · Lower odour.
- Improved wet scrub resistance.
- · Lowering of MFFT.
- · Early rain resistance.

In solvent borne systems ADDAPTOL™ DB has the following advantages:

- · Excellent tail solvent.
- Improved levelling and pinhole resistance.











Technical Data Sheet

ADDAPTOL™ DB **Coalescing Agent**

AT86948 Article number: 18/02/2025 Verification date: Version: 3 1

Please read Safety Data Sheet (SDS) before handling. Safety and Handling

Product Specification This information is available on request through our local representative.

This information is available on request through our local representative. **Packaging**

The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away Storage

from light. For more safety details read the Safety Data Sheet (SDS)

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements

agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO -

Standard 9001:2015.

Liabilities All recommendations for the use of our products, whether given by us in writing, orally, or to be implied

from the results of tests carried out by us, are based on the current state of our knowledge.

Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general

conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: + 31 (0)492 597575

E-mail: info@addapt-chem.com

Home page: http://www.addapt-chem.com







