

### Typical chemical and physical properties

Biodegradable and emulsifiable anti-corrosion additive for aqueous systems. It protects copper, aluminium as well as magnesium and combinations thereof.

#### Proprietary blend of phosphates and glycol ethers.

Appearance	Liquid
Solubility	
Water	Emulsifiable
Odour	Aromatic
Density at 25°C	1,01 - 1,05 g/ml
pH at 25°C	6,5 - 8,5
Viscosity at 25°C	100 - 200 mPa·s

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

### Application and treat level

Markets	Metalworking industry Machinery industry Textile industry Coating industry
Applications	Metalworking fluids (water-based) Ester-based hydraulic fluids (HF-C, HF-A) Textile fluids Coatings
Recommended dosage/usage	0,2 to 2,0 % on total formulation

### Key benefits

#### - Readily biodegradable -

- Excellent long-term corrosion protection in DTM formulations.
- Excellent compatibility with water-based DTM coatings.
- This additive is specially developed for the aeronautic and related industries.
- Exhibits excellent anti-staining and anti-corrosion properties for different grades of aluminium surfaces.
- Can be used in any water-based system that comes into contact with different grades of copper/bronze.
- Product is pH neutral and emulsifiable in water.
- Controls "pitting" of the metal surface.
- Very low foaming.
- Its use is not restricted by the water hardness.

<b>Safety and Handling</b>	Please read Safety Data Sheet (SDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.
<b>Storage</b>	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

**Quality Policy** The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

**Liabilities** *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

