

### Typical chemical and physical properties

Cost-effective foam control agent for emulsion systems based on PVAC, VA/VeoVa, styrene-acrylics or pure acrylics. It is biodegradable and has a high sustainable content.

**Proprietary blend of PAGs and surface-active compounds, largely based on renewable resources.**

Appearance	Liquid
Active content	~100%
Solubility	
Water	Emulsifiable
Mineral oil	Miscible
Density at 25°C	0,89 - 0,91 g/ml
Viscosity at 25°C	40 - 250 mPa·s

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

### Application and treat level

Markets	Coating industry Adhesive industry Cleaning industry Water treatment industry
Applications	Paints Adhesive Floor polish Wastewater treatment
Recommended dosage/usage	0,15 to 0,30 % wt. based on total formulation  2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage

**Suitable as Incidental food contact**

### Key benefits

- Readily biodegradable -- Biobased -- APEO/NPEO free -- Free of MOSH/MOAH -- Free of silicone oils -- Free of amines -- Free of nitrates -- Free of nitrites -
- Suitable for use in pigmented emulsion paints, printing inks as well as emulsion-based adhesives.
- Very suitable for cost-effective, high PVC emulsion paints.
- Maintains the defoaming properties over a prolonged period of time.
- Easily emulsifiable.
- No intercoat adhesion problems are expected when the defoamer is applied.

<b>Safety and Handling</b>	Please read Safety Data Sheet (SDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.
<b>Storage</b>	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

**Quality Policy** The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

**Liabilities** *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

